

REMARKS

The above-noted cancellation of claims 1-5, and addition of new claims 6-10, as well as the submission of a new Abstract and revisions to the Specification, are respectfully submitted prior to initiation of the prosecution of this application in the U.S. Patent and Trademark Office.

The above-noted new claims are respectfully submitted in order to more clearly and appropriately claim the subject matter which applicants consider to constitute their inventive contribution. No new matter is included in these amendments. In addition, the revisions to the Abstract and Specification are submitted in order to clarify and correct the Abstract and Specification and to conform them to all of the requirements of U.S. practice. No new matter is included in these amendments.

In view of the above, it is respectfully requested that these amendments now be entered, and that prosecution on the merits of this application now be initiated. If, however, for any reason the Examiner does not believe such action can be taken, it is respectfully requested that he telephone applicant's attorney at (908) 654-5000 in order to overcome any objections which he may have.

If there are any additional charges in connection with this requested amendment, the Examiner is authorized to charge applicant's Deposit Account No. 12-1095 therefor.

Respectfully submitted,

LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK, LLP



ARNOLD H. KRUMHOLZ
Reg. No. 25,428

600 South Avenue West
Westfield, NJ 07090-1497
Telephone: (908) 654-5000
Facsimile: (908) 654-7866
319393_1.DOC

METHOD AND ARRANGEMENT FOR THE PRODUCTION
OF LIGNOCELLULOSE-CONTAINING BOARDSFIELD OF THE INVENTION

[0001] The present invention relates to a method of ~~producing for~~ continuously producing lignocellulose-containing boards. More particularly, the present invention relates in accordance with the preamble of claim 1, and to apparatus an arrangement for carrying out such a the method in accordance with the preamble of claim 5.

BACKGROUND OF THE INVENTION

[0002] Methods of producing lignocellulose-containing board are well known in to the art, and have found wide use in practice. The manufacture of such boards includes the following main ~~method~~ steps: disintegration of the raw material into particles and/or ~~fibres~~ fibers of appropriate size, drying the particles and/or ~~fibres~~ fibers to a predetermined moisture quotient, and glue-coating the material either prior to or subsequent to the said drying process, shaping the glue-coated material to form a mat, which may comprise several layers, and optionally cold pre-pressing the mat, preheating the said mat, water-spraying mat surfaces, etc., and heat pressing the mat in a discontinuous press or in a continuous press while simulataneously ~~simultaneously~~ subjecting the material ~~simultaneously to heat and pressure and heat~~ so as to obtain a finished board. It is difficult to control the quality of the boards produced in accordance with this known method with respect to the moisture content, temperature and dimensional stability of the boards. When the boards leave the heat pressing state of ~~in~~ the production process, they have a temperature in excess of 100°C and a corresponding ~~vapour~~ vapor pressure. The temperature of the board surfaces falls rapidly to beneath 100°C as the enclosed moisture is vaporised by virtue of a so-called flash effect. The boards are then cooled in ~~so-called~~ cooling wheels. As a result, the boards will obtain a moisture content of about 6%- to 7% after intermediate storage of the board over a period of a day or

two. In many applications this creates a problem, particularly in environments which ~~that~~ have a higher average relative humidity, since the boards will take up moisture when used and thus ~~therewith~~ undergo dimensional changes, as in the case of all lignocellulose-containing materials. One way of counteracting this is to spray water on the boards as they leave the press.

[0003] Another known phenomenon ~~phenomena~~ is that boards produced in this manner ~~way~~ obtain ~~mutually~~ different moisture contents in the surface layers relative to the core layer. If the boards are used for some type of surface treatment, for instance, such as lamination, without having earlier equalised the difference in moisture content, the dimensions of the board may change when this equalisation takes place, ~~in time~~ so that the surface layer loosens. In order to achieve desired equalisation between the various layers, it is customary to thus store the boards for a number of weeks.

[0004] Another known problem is that the boards are not dimensionally stable when they leave the press. This is noticeable primarily because the boards shrink or swell over a process that can take one or more days. Consequently, calibration grinding of the boards is not normally undertaken until the boards have been stored in intermediate storage locations over a number of days.

[0005] Another known problem is that the boards are too hot to be stacked and stored when leaving the hot press. If the boards are too hot when stacked, the glue joints may begin to break down, and the boards will ~~consequently be~~ weakened. This problem is normally alleviated by keeping the boards in a ~~so-called~~ cooling wheel, in which the board temperature is lowered by natural convection.

[0006] It will be evident from the foregoing that the conventionally used press ~~technique~~ and board production techniques involve a number of cost-inducing handling stages and intermediate storage subsequent to the actual board manufacturing process. Accordingly, ~~the~~ one object of the

present invention is to stabilise a board with respect to its moisture content, temperature and dimensional stability in a continuous process, and in that manner therewith avoid cost-inducing handling and storage of the board. Because dimensional stability is achieved, the boards may also be ground or sanded down to a final thickness directly after manufacture. ~~This object is achieved with the method and the apparatus defined in the characterizing clauses of respective claims.~~

SUMMARY OF THE INVENTION

[0007] In accordance with the present invention, these and other objects have now been realized by the invention of a method for continuously producing lignocellulose-containing boards comprising providing a mat of disintegrated, glue-coated and dried lignocellulose-containing material, pressing the mat into a board in a steam injection press, conditioning the board by drawing a predetermined volume of air having a predetermined moisture content at a predetermined temperature through the board by means of suction applied through the board, and grinding the conditioned board to a final thickness directly following the conditioning step. In a preferred embodiment, the conditioning of the board comprises a first conditioning of the board by drawing a first predetermined volume of air having a first predetermined moisture content at a first predetermined temperature through the board in a first direction by means of suction applied through the board, and including a second conditioning of the board by drawing a second predetermined volume of air having a second predetermined moisture content at a second predetermined temperature through the board in a second direction by means of suction applied through the board, wherein the second direction is opposite to the first direction.

[0008] In accordance with one embodiment of the method of the present invention, the pressing of the mat into the board provides a board having a pair of surface layers and a center

layer, and wherein the pair of surface layers and the center layer have substantially the same density.

[0009] In accordance with the present invention, these and other objects have also been realized by the invention of apparatus for continuously providing lignocellulose-containing boards from a mat of disintegrated, glue-coated and dried lignocellulose-containing material, the apparatus comprising a steam injection press for pressing the mat into a board, conditioning means comprising an air supply unit for passing the air through the board as the board passes through a conditioning zone, and a grinder for grinding the conditioned board to a final thickness directly following the conditioning zone. In a preferred embodiment, the conditioning means comprises first conditioning means comprising a first air supply unit for passing the air through the board in a first direction and including second conditioning means comprising a second air supply unit for passing the air through the board in a second direction, the second direction being opposite to the first direction.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The present invention will now be described in more detail with reference to the following detailed description which, in turn, refers to the accompanying drawing, in which:

[0011] The figure is a side, elevational, schematic longitudinal sectional view of a plant constructed in accordance with the present invention.

DETAILED DESCRIPTION

[0012] The plant illustrated in the drawing is based on the plant disclosed in Swedish Patent No. 504,638SE-504-638, which describes a continuous steam injection process. Turning to the drawing, a A—mat 1 formed from lignocellulose-containing material is fed into a continuous steam injection press 2 and there—pressed into boards 3 therein. The boards exiting from the continuous steam injection press 2 enter an after-conditioning zone 4. In the illustrated example, the zone 4 includes two after-conditioning units, 5 and 6. The boards can

after manufacture showed that boards which had passed through the after-conditioning zone retained their thickness, whereas boards that had not passed through ~~said~~that zone were often liable to shrink up to 1 mm within a day or two, in the same way ~~as~~that conventionally manufactured board also shrinks.

[0017] Conventionally produced boards have an enhanced density at their surfaces. However, because it is possible to produce boards in the steam injection press ~~boards~~ that do not have an enhanced surface density, the air throughflow and therewith conditioning of the board and lowering of its temperature can be effected more quickly than in the case of conventional board handling techniques.

[0018] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

after manufacture showed that boards which had passed through the after-conditioning zone retained their thickness, whereas boards that had not passed through ~~said~~ that zone were often liable to shrink up to 1 mm within a day or two, in the same way ~~as~~ that conventionally manufactured board also shrinks.

[0017] Conventionally produced boards have an enhanced density at their surfaces. However, because it is possible to produce boards in the steam injection press ~~boards~~ that do not have an enhanced surface density, the air throughflow and therewith conditioning of the board and lowering of its temperature can be effected more quickly than in the case of conventional board handling techniques.

[0018] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

318657_1.DOC